

【正誤表】

WSP039-2005

フランジ付ポリエチレン粉体ライニング鋼管

頁	誤	正																																																																																																																																																																																								
P10	<p>付表1 ライニング管の寸法</p> <p>単位：mm</p> <table border="1"> <thead> <tr> <th rowspan="4">原管</th> <th rowspan="4">呼び径 (A)</th> <th colspan="4">ライニング管</th> <th rowspan="4">内面ライニング 厚さ</th> <th rowspan="4">外面ライニング 厚さ</th> </tr> <tr> <th colspan="2">鋼管部</th> <th rowspan="3">外径</th> <th rowspan="3">継手</th> </tr> <tr> <th colspan="2">外径許容差</th> </tr> <tr> <th>直管</th> <th>継手</th> </tr> </thead> <tbody> <tr> <td rowspan="14">SGP STPG</td> <td>20</td> <td>27.2</td> <td rowspan="4">±0.5%</td> <td rowspan="4">±2.0%</td> <td rowspan="4">0.5 以上</td> <td rowspan="4">0.5 以上</td> </tr> <tr> <td>25</td> <td>34.0</td> </tr> <tr> <td>32</td> <td>42.7</td> </tr> <tr> <td>40</td> <td>48.6</td> </tr> <tr> <td>50</td> <td>60.5</td> <td rowspan="4">±1.0%</td> <td rowspan="4">±2.5%</td> <td rowspan="4">0.8 以上</td> <td rowspan="4">0.8 以上</td> </tr> <tr> <td>65</td> <td>76.3</td> </tr> <tr> <td>80</td> <td>89.1</td> </tr> <tr> <td>100</td> <td>114.3</td> </tr> <tr> <td>125</td> <td>139.8</td> <td rowspan="4">±1.6%</td> <td rowspan="4">±3.5%</td> <td rowspan="4">1.0 以上</td> <td rowspan="4">1.0 以上</td> </tr> <tr> <td>150</td> <td>165.2</td> </tr> <tr> <td>200</td> <td>216.3</td> </tr> <tr> <td>250</td> <td>267.4</td> </tr> <tr> <td rowspan="10">STPY</td> <td>300</td> <td>318.5</td> <td rowspan="6">±0.8%</td> <td rowspan="6">+5.0% -4.5%</td> <td rowspan="6">1.0 以上</td> <td rowspan="6">1.0 以上</td> </tr> <tr> <td>350</td> <td>355.6</td> </tr> <tr> <td>400</td> <td>406.4</td> </tr> <tr> <td>450</td> <td>457.2</td> </tr> <tr> <td>500</td> <td>508.0</td> </tr> <tr> <td>550</td> <td>558.8</td> </tr> <tr> <td>600</td> <td>609.6</td> <td rowspan="4">±0.5% (周長)</td> <td rowspan="4">+6.4% -4.8%</td> </tr> <tr> <td>650</td> <td>660.4</td> </tr> <tr> <td>700</td> <td>711.2</td> </tr> <tr> <td>750</td> <td>762.0</td> </tr> <tr> <td>800</td> <td>812.8</td> </tr> <tr> <td>850</td> <td>863.6</td> </tr> <tr> <td>900</td> <td>914.4</td> </tr> <tr> <td>1 000</td> <td>1 016.0</td> </tr> <tr> <td>1 100</td> <td>1 117.6</td> </tr> <tr> <td>1 200</td> <td>1 219.2</td> </tr> </tbody> </table>	原管	呼び径 (A)	ライニング管				内面ライニング 厚さ	外面ライニング 厚さ	鋼管部		外径	継手	外径許容差		直管	継手	SGP STPG	20	27.2	±0.5%	±2.0%	0.5 以上	0.5 以上	25	34.0	32	42.7	40	48.6	50	60.5	±1.0%	±2.5%	0.8 以上	0.8 以上	65	76.3	80	89.1	100	114.3	125	139.8	±1.6%	±3.5%	1.0 以上	1.0 以上	150	165.2	200	216.3	250	267.4	STPY	300	318.5	±0.8%	+5.0% -4.5%	1.0 以上	1.0 以上	350	355.6	400	406.4	450	457.2	500	508.0	550	558.8	600	609.6	±0.5% (周長)	+6.4% -4.8%	650	660.4	700	711.2	750	762.0	800	812.8	850	863.6	900	914.4	1 000	1 016.0	1 100	1 117.6	1 200	1 219.2	<p>付表1 ライニング管の寸法</p> <p>単位：mm</p> <table border="1"> <thead> <tr> <th rowspan="4">原管</th> <th rowspan="4">呼び径 (A)</th> <th colspan="4">ライニング管</th> <th rowspan="4">内面ライニング 厚さ</th> <th rowspan="4">外面ライニング 厚さ</th> </tr> <tr> <th colspan="2">鋼管部</th> <th rowspan="3">外径</th> <th rowspan="3">継手</th> </tr> <tr> <th colspan="2">外径許容差</th> </tr> <tr> <th>直管</th> <th>継手</th> </tr> </thead> <tbody> <tr> <td rowspan="14">SGP STPG</td> <td>20</td> <td>27.2</td> <td rowspan="4">±0.5%</td> <td rowspan="4">±2.0%</td> <td rowspan="4">0.5 以上</td> <td rowspan="4">0.5 以上</td> </tr> <tr> <td>25</td> <td>34.0</td> </tr> <tr> <td>32</td> <td>42.7</td> </tr> <tr> <td>40</td> <td>48.6</td> </tr> <tr> <td>50</td> <td>60.5</td> <td rowspan="4">±1.0%</td> <td rowspan="4">±2.5%</td> <td rowspan="4">0.8 以上</td> <td rowspan="4">0.8 以上</td> </tr> <tr> <td>65</td> <td>76.3</td> </tr> <tr> <td>80</td> <td>89.1</td> </tr> <tr> <td>100</td> <td>114.3</td> </tr> <tr> <td>125</td> <td>139.8</td> <td rowspan="4">±1.6%</td> <td rowspan="4">±3.5%</td> <td rowspan="4">1.0 以上</td> <td rowspan="4">1.0 以上</td> </tr> <tr> <td>150</td> <td>165.2</td> </tr> <tr> <td>200</td> <td>216.3</td> </tr> <tr> <td>250</td> <td>267.4</td> </tr> <tr> <td rowspan="10">STPY</td> <td>300</td> <td>318.5</td> <td rowspan="6">±0.8%</td> <td rowspan="6">+5.0% -4.5%</td> <td rowspan="6">1.0 以上</td> <td rowspan="6">1.0 以上</td> </tr> <tr> <td>350</td> <td>355.6</td> </tr> <tr> <td>400</td> <td>406.4</td> </tr> <tr> <td>450</td> <td>457.2</td> </tr> <tr> <td>500</td> <td>508.0</td> </tr> <tr> <td>550</td> <td>558.8</td> </tr> <tr> <td>600</td> <td>609.6</td> <td rowspan="4">±0.5% (周長)</td> <td rowspan="4">+6.4% -4.8%</td> </tr> <tr> <td>650</td> <td>660.4</td> </tr> <tr> <td>700</td> <td>711.2</td> </tr> <tr> <td>750</td> <td>762.0</td> </tr> <tr> <td>800</td> <td>812.8</td> </tr> <tr> <td>850</td> <td>863.6</td> </tr> <tr> <td>900</td> <td>914.4</td> </tr> <tr> <td>1 000</td> <td>1 016.0</td> </tr> <tr> <td>1 100</td> <td>1 117.6</td> </tr> <tr> <td>1 200</td> <td>1 219.2</td> </tr> </tbody> </table>	原管	呼び径 (A)	ライニング管				内面ライニング 厚さ	外面ライニング 厚さ	鋼管部		外径	継手	外径許容差		直管	継手	SGP STPG	20	27.2	±0.5%	±2.0%	0.5 以上	0.5 以上	25	34.0	32	42.7	40	48.6	50	60.5	±1.0%	±2.5%	0.8 以上	0.8 以上	65	76.3	80	89.1	100	114.3	125	139.8	±1.6%	±3.5%	1.0 以上	1.0 以上	150	165.2	200	216.3	250	267.4	STPY	300	318.5	±0.8%	+5.0% -4.5%	1.0 以上	1.0 以上	350	355.6	400	406.4	450	457.2	500	508.0	550	558.8	600	609.6	±0.5% (周長)	+6.4% -4.8%	650	660.4	700	711.2	750	762.0	800	812.8	850	863.6	900	914.4	1 000	1 016.0	1 100	1 117.6	1 200	1 219.2
原管	呼び径 (A)			ライニング管						内面ライニング 厚さ	外面ライニング 厚さ																																																																																																																																																																															
				鋼管部		外径	継手																																																																																																																																																																																			
				外径許容差																																																																																																																																																																																						
		直管	継手																																																																																																																																																																																							
SGP STPG	20	27.2	±0.5%	±2.0%	0.5 以上	0.5 以上																																																																																																																																																																																				
	25	34.0																																																																																																																																																																																								
	32	42.7																																																																																																																																																																																								
	40	48.6																																																																																																																																																																																								
	50	60.5	±1.0%	±2.5%	0.8 以上	0.8 以上																																																																																																																																																																																				
	65	76.3																																																																																																																																																																																								
	80	89.1																																																																																																																																																																																								
	100	114.3																																																																																																																																																																																								
	125	139.8	±1.6%	±3.5%	1.0 以上	1.0 以上																																																																																																																																																																																				
	150	165.2																																																																																																																																																																																								
	200	216.3																																																																																																																																																																																								
	250	267.4																																																																																																																																																																																								
	STPY	300	318.5	±0.8%	+5.0% -4.5%	1.0 以上	1.0 以上																																																																																																																																																																																			
		350	355.6																																																																																																																																																																																							
400		406.4																																																																																																																																																																																								
450		457.2																																																																																																																																																																																								
500		508.0																																																																																																																																																																																								
550		558.8																																																																																																																																																																																								
600		609.6	±0.5% (周長)	+6.4% -4.8%																																																																																																																																																																																						
650		660.4																																																																																																																																																																																								
700		711.2																																																																																																																																																																																								
750		762.0																																																																																																																																																																																								
800	812.8																																																																																																																																																																																									
850	863.6																																																																																																																																																																																									
900	914.4																																																																																																																																																																																									
1 000	1 016.0																																																																																																																																																																																									
1 100	1 117.6																																																																																																																																																																																									
1 200	1 219.2																																																																																																																																																																																									
原管	呼び径 (A)	ライニング管				内面ライニング 厚さ	外面ライニング 厚さ																																																																																																																																																																																			
		鋼管部		外径	継手																																																																																																																																																																																					
		外径許容差																																																																																																																																																																																								
		直管	継手																																																																																																																																																																																							
SGP STPG	20	27.2	±0.5%	±2.0%	0.5 以上	0.5 以上																																																																																																																																																																																				
	25	34.0																																																																																																																																																																																								
	32	42.7																																																																																																																																																																																								
	40	48.6																																																																																																																																																																																								
	50	60.5	±1.0%	±2.5%	0.8 以上	0.8 以上																																																																																																																																																																																				
	65	76.3																																																																																																																																																																																								
	80	89.1																																																																																																																																																																																								
	100	114.3																																																																																																																																																																																								
	125	139.8	±1.6%	±3.5%	1.0 以上	1.0 以上																																																																																																																																																																																				
	150	165.2																																																																																																																																																																																								
	200	216.3																																																																																																																																																																																								
	250	267.4																																																																																																																																																																																								
	STPY	300	318.5	±0.8%	+5.0% -4.5%	1.0 以上	1.0 以上																																																																																																																																																																																			
		350	355.6																																																																																																																																																																																							
400		406.4																																																																																																																																																																																								
450		457.2																																																																																																																																																																																								
500		508.0																																																																																																																																																																																								
550		558.8																																																																																																																																																																																								
600		609.6	±0.5% (周長)	+6.4% -4.8%																																																																																																																																																																																						
650		660.4																																																																																																																																																																																								
700		711.2																																																																																																																																																																																								
750		762.0																																																																																																																																																																																								
800	812.8																																																																																																																																																																																									
850	863.6																																																																																																																																																																																									
900	914.4																																																																																																																																																																																									
1 000	1 016.0																																																																																																																																																																																									
1 100	1 117.6																																																																																																																																																																																									
1 200	1 219.2																																																																																																																																																																																									